



X-TREME 160R

0-60 km/h in **4.7 sec***

SPECIFICATIONS

ENGINE

ENGINE TYPE	AIR COOLED, 4 STROKE 2 VALVE SINGLE CYLINDER OHC
DISPLACEMENT	163 cc
MAX POWER	11.2 kw (15 bhp) @ 8500 revolutions per minute
MAX TORQUE	14 Nm @ 6500 revolutions per minute
FUEL SYSTEM	ADVANCED PROGRAMMED FUEL INJECTION
STARTING	SELF & KICK

TRANSMISSION & CHASSIS

CLUTCH	MULTI PLATE WET CLUTCH
GEARBOX	5 SPEED CONSTANT MESH
FRAME TYPE	TUBULAR DIAMOND

SUSPENSION

FRONT	TELESCOPIC (37 mm DIA) WITH ANTI FRICTION BUSH
REAR	7 STEP RIDER-ADJUSTABLE MONOSHOCK

BRAKES

FRONT BRAKE TYPE	276 mm PETAL DISC, SINGLE CHANNEL ABS
REAR BRAKE TYPE	220 mm PETAL DISC 130 mm DRUM

TYRES

FRONT TYRE	100/80-17 (TUBELESS)
REAR TYRE	130/70 -R17 RADIAL (TUBELESS)

ELECTRICALS

SPEEDOMETER	INVERTED LCD CONSOLE
HEAD LIGHT	FULL LED WITH LED DRLS

DIMENSIONS

LENGTH X WIDTH X HEIGHT	2029 X 793 X 1052 mm
WHEELBASE	1327 mm
SEAT HEIGHT	790 mm
GROUND CLEARANCE	167 mm

WEIGHTS

KERB WEIGHT	139.5 kg 138.5 kg
FUEL TANK CAPACITY	12 Litre

*Figures highlighted in red indicate specification for Double Disc variant

AVAILABLE IN ATTRACTIVE COLOURS



PEARL SILVER WHITE

SPORTS RED

VIBRANT BLUE

Hero Xtreme 160 R complies with B96 emission norms. It is our endeavour to constantly improve our products. This could lead to changes in product specifications without notice. Accessories shown may not be part of standard fitment. Always wear a helmet while riding a two-wheeler.

Hero MotoCorp Ltd. Regd. The Grand Plaza, Plot No. 2, Nelson Mandela Road, Vasant Kunj, Phase - II, New Delhi - 110070, India. CIN: L35911DL1984PLC017354 For more information, call Toll Free No.: 1800-266-0018 or visit www.heromotocorp.com



*Conditions apply

*Under standard test conditions *First in the 150/160cc naked motorcycle segment